

First aid for external files and packages that need updating

Frank Mittelbach, L^AT_EX Project

2026-10-02

Abstract

This file contains some first aid for packages or classes that require updates because of internal changes to L^AT_EX but that aren't yet reflected in the package/class code.

Contents

1	Introduction	2
1.1	Minor kernel fixes	2
2	The Implementation	2
2.1	The filehook package first aid	3
2.2	The dinbrief class first aid	5
2.3	The unicode-math package first aid	5
2.4	The pgfpages and pgfmorepages first aid	5
2.5	The babel package	6
2.6	The songs package first aid	6
2.7	The crop package first aid	6
2.8	The bigfoot first aid	7
2.9	marginfix first aid	7
2.10	ulem first aid	8
2.11	varwidth first aid	8
2.12	The german class first aid	9
2.13	The underscore first aid	9
2.14	The acro package first aid	10
2.15	The chemformula package first aid	10
2.16	The chemnum package first aid	10
2.17	The cleveref package first aid	10
2.18	The zref-clever package first aid	13
2.19	The subcaption package first aid	14
2.20	The arydshln package first aid	14
2.21	The calc package first aid	14
2.22	First aid after retiring the legacy mark mechanism	15
2.23	First aid for morewrites	15
2.24	First aid for AMS classes	16
2.25	The cellspace package first aid	18

1 Introduction

Over the years package writers have hooked into various parts of internal $\text{\LaTeX}$ commands (largely because proper interfaces were missing in important places) and if we are now gradually adding such interfaces these internal commands do change and as a result patching into them stops working.

As part of making such internal changes the $\text{\LaTeX}$ Project team attempts to check for such usage in packages, alert the package maintainers and ensures that the packages get updated alongside the core $\text{\LaTeX}$ system. However it is not always possible to get packages that will fail with a new kernel updated in time and if that is the case we try to provide a temporary fix in this file for them. Once the package gets updated the fix will then be removed again.

For that reason, it is put into a separate bundle so that we can update it easily without requiring the CTAN maintainers to install a new full $\text{\LaTeX}$ system just because we take out (or add) a fix for a package here.

In the best case scenario the file documented here should be empty. In practice it will probably always contain one or the other fix while we are waiting for the package to get updated.

Important notice: The fixes provided here are not meant to be a permanent solution, but are only provided to support the transition period. They are (usually) neither complete nor necessarily the best solution! Furthermore, as they are done from the “outside”, they usually add some burden and slow down $\text{\LaTeX}$ processing, even if the package/class is not used in the document.

We will therefore remove such code as soon as possible again. In practice this means that if some package never gets updated/corrected, then it will eventually fail to work, because after one or at most two $\text{\LaTeX}$ releases we will take out the transition code to ensure that this “first aid patching” doesn’t get out of bounds.

1.1 Minor kernel fixes

If we encounter issues with the kernel code that should get fixed before the next main release we normally generate a patch release for $\text{\LaTeX}$. However, depending on the complexity of the fix we might first add the fix here and generate a full patch release only when a number of such issues have accumulated. This way we lessen the impact on CTAN maintainers because for each tach release we have to make and distribute also a matching development release.

2 The Implementation

This file is meant to be loaded during format generation which is why we give it the extension `.ltx`.

```
1 <*kernel>
2 \def\LaTeXFirstAidDate{2026-10-02}
3 \def\LaTeXFirstAidVersion{v1.1z}
4 \ProvidesFile{latex2e-first-aid-for-external-files.ltx}
5           [\LaTeXFirstAidDate\space \LaTeXFirstAidVersion\space
```

`\FirstAidNeededT` This is a very simple help to ensure that we only apply first aid to an unmodified package or class. It only works in the case the file has already been loaded and the `\csname \ver@#1.#2` got defined (holding the current date, version, and short description info). We then compare its content to a frozen string and make the modification `#3` only if both agree. If they differ we assume that the package/class in question got updated by its maintainer.

```

7 \ExplSyntaxOn
8 \cs_new:Npn\FirstAidNeededT#1#2#3{
9   \exp_args:Nce\str_if_eq:onTF{ver@#1.#2}{#3}
10    { \typeout{==>~ First~ Aid~ for~ #1.#2~ applied! } }
11    { \typeout{==>~ First~ Aid~ for~ #1.#2~ no~ longer~ applied!^^J
12      \@spaces Expected:^^J
13      \@spaces\@spaces #3^^J
14      \@spaces but~ found:^^J
15      \@spaces\@spaces \use:c{ver@#1.#2}^^J
16      \@spaces so~ I'm~ assuming~ it~ got~ fixed.
17    } }
18   \exp_args:Nce\str_if_eq:onT{ver@#1.#2}{#3}
19 }
20 \ExplSyntaxOff
21 </kernel>

```

2.1 The filehook package first aid

The filehook package implements hooks into file loading commands. These days this is already provided by the kernel albeit not with the same user interface. Until that package gets updated (to use the kernel interfaces) we provide a substitution. This does not offer all hooks from filehook but all that have been used in packages available in T_EX Live.

Note that this doesn't fix `currfile` because that package uses filehook but relies on the internals of the old implementation.

The package has now got an update so we aren't activating the first aid. However, at the moment it basically bypasses the new hook mechanism and puts the old hooks in thereby disabling, for example, the possibility to re-order code through rules.

We therefore keep `filehook-ltx.sty` around as a guideline for further updates.

Replacing filehook with a leaner version would then work like this:

```

22 <*kernel>
23 %\declare@file@substitution{filehook.sty}{filehook-ltx.sty}
24 </kernel>

```

What follows is a simplified (partial) implementation of the filehook interfaces. Not implemented are:

```

\AtBeginOfFiles      \AtEndOfFiles
\AtBeginOfInputs     \AtEndOfInputs
\AtBeginOfInputFile  \AtEndOfInputFile
25 <*filehook-ltx>

```

```

26 \newcommand\AtBeginOfEveryFile [1]
27   {\AddToHook{file/before}{#1}}
28 \newcommand\AtEndOfEveryFile [1]
29   {\AddToHook{file/after}{#1}}

30 \newcommand\AtBeginOfIncludes [1]
31   {\AddToHook{include/before}{#1}}
32 \newcommand\AtEndOfIncludes [1]
33   {\AddToHook{include/end}{#1}}
34 \newcommand\AfterIncludes [1]
35   {\AddToHook{include/after}{#1}}

36 \newcommand\AtBeginOfPackages [1]
37   {\AddToHook{package/before}{#1}}
38 \newcommand\AtEndOfPackages [1]
39   {\AddToHook{package/after}{#1}}

40 \newcommand\AtBeginOfClasses [1]
41   {\AddToHook{class/before}{#1}}
42 \newcommand\AtEndOfClasses [1]
43   {\AddToHook{class/after}{#1}}

44 \newcommand\AtBeginOfFile [2]
45   {\AddToHook{file/#1/before}{#2}}
46 \newcommand\AtEndOfFile [2]
47   {\AddToHook{file/#1/after}{#2}}

```

Some commands offered a starred form

```

48 \DeclareDocumentCommand \AtBeginOfPackageFile {smm}
49   {\IfBooleanTF{#1}%
50     {\@ifpackageloaded{#2}%
51       {#3}%
52       {\AddToHook{package/#2/before}{#3}}}%
53     {\AddToHook{package/#2/before}{#3}}%
54   }

55 \DeclareDocumentCommand \AtEndOfPackageFile {smm}
56   {\IfBooleanTF{#1}%
57     {\@ifpackageloaded{#2}%
58       {#3}%
59       {\AddToHook{package/#2/after}{#3}}}%
60     {\AddToHook{package/#2/after}{#3}}%
61   }

```

Are the * forms here of any use? I know they are use 3–4 times on CTAN but I wonder if those are real or mistaken usages.

```

62 \DeclareDocumentCommand \AtBeginOfClassFile {smm}
63   {\IfBooleanTF{#1}%
64     {\@ifclassloaded{#2}%
65       {#3}%
66       {\AddToHook{class/#2/before}{#3}}}%
67     {\AddToHook{class/#2/before}{#3}}%
68   }

69 \DeclareDocumentCommand \AtEndOfClassFile {smm}
70   {\IfBooleanTF{#1}%
71     {\@ifclassloaded{#2}%
72       {#3}%

```

```

73         {\AddToHook{class/#2/after}{#3}}}%
74     {\AddToHook{class/#2/after}{#3}}%
75 }
76 \newcommand\AtBeginOfIncludeFile [2]
77   {\AddToHook{include/#1/before}{#2}}
78 \newcommand\AtEndOfIncludeFile [2]
79   {\AddToHook{include/#1/end}{#2}}
80 \newcommand\AfterIncludeFile [2]
81   {\AddToHook{include/#1/after}{#2}}
82 </filehook-ltx>
83 <*kernel>

```

2.2 The `dinbrief` class first aid

Again a case of a no longer correct `\endgroup` in document. Here the fix is simply though.

```

84 \AddToHook{file/dinbrief.cls/after}[firstaid]{%
85   \FirstAidNeededT{dinbrief}{cls}{2000/03/02 LaTeX2e class}%
86   {\AddToHook{env/document/begin}{\begingroup}}%
87 }

```

2.3 The `unicode-math` package first aid

If `unicode-math` is used together with `doc` there is a problem because it changes the mathcodes without adjusting the use in `doc` that assume standard settings. Could be fixed on either side, but as `unicode-math` is derivating from the standard, the right place is probably a fix in this package. For now we do it here. See [github/820](https://github.com/TeXmacs/820).

```

88 \AddToHook{package/unicode-math/after}{%
89   \AddToHook{cmd/mod@math@codes/after}{\mathcode'\|=28796 }}

```

2.4 The `pgfpages` and `pgfmorepages` first aid

`pgfpages` alters the `\shipout` primitive to support multiple page up scenarios. If used together with `atbegshi` that worked because the alterations done by `atbegshi` came later and so used the new definition provide by `pgfpages`. Now that the code from `atbegshi` is already in the kernel this further redefinition doesn't happen with the result that the change to `\shipout` comes to late and breaks the kernel processes.

```

90 \ExplSyntaxOn
91 \AddToHook{file/pgfpages.sty/after}[firstaid]{

```

Undo overwriting `\shipout`:

```

92   \cs_gset_eq:NN \shipout \pgfpages@originalshipout

```

Instead overwrite the L3 programming layer name of the primitive. This is really an absolute no-go, but for now the simplest solution to keep the original code running.

It will be replaced when the “configuration points” interface for L^AT_EX becomes available. At that point the package will be able to set up a different strategy for doing shipouts and without the need to overwrite a primitive (which it did in the past and which we do below) and then this code here can be taken out again.

```

93 \cs_set_eq:NN \pgfpages@originalshipout \tex_shipout:D
94 \cs_set_eq:NN \tex_shipout:D \pgfpages@interceptshipout
95 }
96 \ExplSyntaxOff

```

Same issue with `pgfmorepages` but slightly different implementation (sigh).

```

97 \ExplSyntaxOn
98 \AddToHook{file/pgfmorepages.sty/after}[firstaid]{
99   \cs_set_nopar:Npn \pgfhookintoshipout {
100     \cs_set_eq:NN \pgfpages@originalshipout \tex_shipout:D
101     \cs_set_eq:NN \tex_shipout:D \pgfpages@interceptshipout
102   }
103 }
104 \ExplSyntaxOff

```

2.5 The `babel` package

Turn off the `babel` hack.

```

105 \AddToHook{file/babel.sty/before}[firstaid]{\def\BabelCaseHack{}}

```

2.6 The `songs` package first aid

The `songs` package uses `\obeylines` and redefines `\par` for special effect. this no longer works in L^AT_EX 2022-06-01 (gh issue 367). The following fixes at least one failure.

```

106 \AddToHook{file/songs.sty/after}[firstaid]{%
107   \FirstAidNeededT{songs}{sty}{2018/09/12 v3.1 Songs package}%
108   {%
109     \renewcommand\SB@obeylines{%
110       \let\obeyedline\SB@par%
111       \obeylines%
112       \let\@par\SB@par%
113     }}%
114 }

```

2.7 The `crop` package first aid

The `crop` packages fails currently due to two L^AT_EX changes: It doesn't know that `\stockheight` and `\stockwidth` are now defined, and doesn't take into account that `\rlap` is robust (<https://github.com/rrthomas/crop/issues/2>). The first is addressed by setting the dimension if they are zero or negative. For the second we locally change the meaning of `\protect`

```

115 \AddToHook{file/crop.sty/after}[firstaid]{%
116   \FirstAidNeededT{crop}{sty}{2017/11/19 1.10 crop marks (mf)}%
117   {%
118     \ifdim\stockwidth > 0pt \else \stockwidth\paperwidth \fi
119     \ifdim\stockheight > 0pt \else \stockheight\paperheight \fi
120     \renewcommand*\CROP@genreflect[1]{%
121       \leavevmode
122       \dimen0\CROP@horigin
123       \kern2\dimen0
124       \begingroup

```

```

125 \set@typeset@protect %change protect
126 \reflectbox{%
127     \hb@xt@\paperwidth{%
128         \vbox to\paperheight{%
129             #1%
130             \vss
131         }%
132     \hss
133 }%
134 }%
135 \endgroup
136 }
137 }%
138 }

```

2.8 The bigfoot first aid

The **bigfoot** packages makes the assumption that two `\newinsert` allocations have a recognisable order in their numbers, the second one has a lower number. This was correct in the classic $\text{\TeX}$ implementation but with the extended allocation possibilities of all modern engines is no longer the case and there is a point where the allocations take a “jump” breaking the ordering assumption. These days we are fairly close to that point and depending on how many packages are loaded before **bigfoot** the package breaks.

This firstaid therefore jumps over the problematical point by pushing the count allocation to a safe value if necessary.

```

139 \AddToHook{file/bigfoot.sty/after}{%
140     \ifnum\count10<\insecunt
141         \global\count10=\insecunt
142     \fi

```

We also correct a bug that **bigfoot** tries to shift mark registers, but in $\text{\LaTeX}$ (at least since 2015) the allocation number is not 266, so it does that to a random number of mark registers (which sometimes blows up depending on the value in 266).

```

143 \def\FN@allmarks#1{\@elt{#1}%
144     \ifnum#1<\count256 %<--- problem: 266 isn't the counter for marks
145         \expandafter\FN@allmarks\expandafter{\number\numexpr#1+\@ne}%
146     \fi}%
147 }

```

2.9 marginfix first aid

The **marginfix** package tries to patch `\@combinefloats` but with 2025-06 the kernel doesn't use this any longer but uses `\@outputbox@attachfloats` instead.

```

148 \AddToHook{file/marginfix.sty/after}[firstaid]{%
149     \FirstAidNeededT{marginfix}{sty}%
150     {2020/05/06 v1.2 Fix Margin Paragraphs}%
151     {\let \@outputbox@attachfloats \@combinefloats}%
152 }

```

2.10 ulem first aid

In 2020 we fixed various kernel commands to accept calc syntax. The ulem package redefines some internals and that now conflicts with the new definitions as they involve an extra group. So we alter the definition of `\@hspace` if ulem was loaded. This is not perfect, obviously, so it will go out the moment ulem gets adjusted.

```
153 \AddToHook{file/ulem.sty/after}[firstaid]{%
154   \def\@hspace#1{\begingroup\setlength\skip@{#1}%
155     \edef\x{\endgroup\hskip\the\skip@\relax}\x}%
156 }
```

2.11 varwidth first aid

The varwidth package does a lot of low-level paragraph manipulation assuming traditional TeX paragraphs. However, with the paragraph hooks we end up with one extra glue Opt item on the vertical list and if that isn't removed then the package doesn't find its penalties.

So this needs to be removed as well by adding an additional `\unskip`.

```
157 \AddToHook{file/varwidth.sty/after}[firstaid]{%
158   \FirstAidNeededT{varwidth}{sty}%
159     {2009/03/30 ver 0.92; \space Variable-width minipages}%
160   {%
161 \def\@vwid@sift{%
162   \skip@\lastskip\unskip
163   \ifdim\lastskip=\z@\unskip\fi % <---- the first aid here (not just unskip)
164   \dimen@\lastkern\unkern
165   \count@\lastpenalty\unpenalty
166   \setbox\z@\lastbox
167   \ifvoid\z@ \advance\sift@deathcycles\@ne \else \sift@deathcycles\z@ \fi
168   \ifnum\sift@deathcycles>33
169     \let\@vwid@sift\relax
170     \PackageWarning{varwidth}{Failed to reprocess entire contents}%
171   \fi
172   \ifnum\count@=\@vwid@preeqp \@vwid@eqmodefalse\fi
173   \ifnum\count@=\@vwid@posteqp \@vwid@eqmodetrue\fi
174   \ifnum\count@=\@vwid@toppen % finished
175     \let\@vwid@sift\relax
176   \else\ifnum\count@=\@vwid@offsets
177     \@vwid@setoffsets
178   \else
179     \ifnum\count@=\@vwid@postw
180     \else
181       \@vwid@resetb % reset box \z@ or measure it
182     \fi
183     \@vwid@append
184   \fi\fi
185   \@vwid@sift}%
186   }%
187 }
```

2.12 The german class first aid

Handling of \protected UTF-8

```

188 \AddToHook{file/german.sty/after}[firstaid]{%
189   \FirstAidNeededT{german}{sty}{1998/07/08 v2.5e Support for writing german texts (br)}
190   {%
191   \let\grmn@active@dq@\@active@dq
192   \def\@active@dq{\protect\grmn@active@dq}%
193   \germanTeX
194   }%
195   }

196 \AddToHook{file/ngerman.sty/after}[firstaid]{%
197   \FirstAidNeededT{ngerman}{sty}{1998/07/08 v2.5e Support for writing german texts (br)}
198   {%
199   \let\grmn@active@dq@\@active@dq
200   \def\@active@dq{\protect\grmn@active@dq}%
201   \ngermanTeX
202   }%
203   }

204 </kernel>

```

2.13 The underscore first aid

The `underscore` package makes the underscore active. This means that the underscore can not be used in label and references unless the package option `strings` is used (which patches a selection of problematic commands like `\label` and `\ref`) or `babel` is used which redefines¹ a selection of problematic commands like `\@testdef` or `\@newl@bel`.

With the new property commands the work-around do not work. We therefore make the underscore protected and use `\ifincsname` to allow its use in csnames.

```

205 <*underscore-ltx>
206 \ProvidesPackage{underscore-ltx}[2023/09/20 LaTeX firstaid to make underscore protected ]
207 \begingroup
208   \catcode'\_=\active
209   \protected\gdef _{%
210     \ifincsname %
211       \string_%
212     \else
213       \ifx\protect\@typeset@protect
214         \ifmmode \sb \else \BreakableUnderscore \fi
215       \else
216         \ifx\protect\@unexpandable@protect \noexpand_%
217         \else \protect_%
218       \fi\fi
219     \fi
220   }
221   \global\let\ActiveUnderscore=_
222 \endgroup
223 </underscore-ltx>

```

¹unless the recommended option `safe=none` is used

```

224 (*kernel)
225 \AddToHook{file/underscore.sty/after}[firstaid]{%
226   \FirstAidNeededT{underscore}{sty}{2006/09/13}{\RequirePackage{underscore-ltx}}
227 }/kernel)
228 (*kernel)

```

2.14 The `acro` package first aid

The package does not declare a `prop`, which causes an issue with newer routines in `expl3`.

```

229 \AddToHook{package/acro/after}[firstaid]{%
230   \FirstAidNeededT{acro}{sty}{2022/04/01 v3.8 typeset acronyms
231     and other abbreviations (CN)}
232   {\UseName{prop_new:c}{l__acro_tmpa_prop}}%

```

With the 2024 June release of L^AT_EX it will also fail to patch `\endlongtable` and therefore errors when loading. However, the patch it tries never worked (because it was setting a local boolean at a point where it was more or less immediately reset). Thus, rather than fixing the patch approach (which requires to surround the patch with `\ExplSyntaxOn \catcode'\_ =10\_ and \ExplSyntaxOff`) we simply disable the patch for now.

```

233   \acsetup{patch/longtable=false}%
234 }%
235 }

```

2.15 The `chemformula` package first aid

Package `chemformula` uses `l3keys2e` for option processing. This used to be made available as `chemformula` also loads `xfrac`, which loaded `l3keys2e`. However, `xfrac` has now been updated to use the newer kernel method if available, so loading `chemformula` fails.

```

236 \AddToHook{package/chemformula/before}[firstaid]{%
237   \RequirePackage{l3keys2e}%
238 }

```

2.16 The `chemnum` package first aid

The package does not declare a `prop`, which causes an issue with newer routines in `expl3`.

```

239 \AddToHook{package/chemnum/after}[firstaid]{%
240   \FirstAidNeededT{chemnum}{sty}{2021/01/21 v1.3a a comprehensive
241     approach for the numbering of chemical compounds (CN)}
242   {\UseName{prop_new:c}{l__chemnum_tmpa_prop}}%
243 }

```

2.17 The `cleveref` package first aid

The `cleveref` package expects only two data containers for its internal `\newlabel` command. This fails if `xr-hyper` is used which expands every `\newlabel` to five data container and puts the file name into the last one.

```

244 \AddToHook{package/cleveref/after}[firstaid]{%

```

```

245 {\input{latex-firstaid-pkg-cleveref.ltx}}
246 \kernel
247 \cleveref

```

These are the two commands which retrieve the data from the label info. We change them to expect five arguments.

```

248 \FirstAidNeededT{cleveref}{sty}{2018/03/27 v0.21.4 Intelligent cross-referencing}{%
249 \def\cref@getref#1#2{%
250 \expandafter\let\expandafter#2\csname r@#1\cref\endcsname%
251 \expandafter\expandafter\expandafter\def%
252 \expandafter\expandafter\expandafter#2%
253 \expandafter\expandafter\expandafter{%
254 \expandafter\@firstoffive#2}}}% <----- five
255 \def\cpageref@getref#1#2{%
256 \expandafter\let\expandafter#2\csname r@#1\cref\endcsname%
257 \expandafter\expandafter\expandafter\def%
258 \expandafter\expandafter\expandafter#2%
259 \expandafter\expandafter\expandafter{%
260 \expandafter\@secondoffive#2}}}% <----- five

```

We also need to redefine the internal label commands of cleveref. This must be done after cleveref has made its changes in `begindocument` so we add it to the same hook using the hook label used by cleveref. This way it is guaranteed to overwrite the definitions.

```

261 \AddToHook{begindocument}[cleveref]{%
262 \def\label@noarg#1{%
263 \cref@old@label{#1}%
264 \@bsphack%
265 \protected@edef\@tempa{{page}}{\the\c@page}}% <--- should be protected
266 \setcounter{page}{1}%
267 \protected@edef\@tempb{\thepage}% <--- should be protected
268 \expandafter\setcounter\@tempa%
269 \cref@constructprefix{page}{\cref@result}%
270 \protected@write\@auxout{%
271 {\string\newlabel{#1\cref}{\cref@currentlabel}%
272 {[\@tempb][\arabic{page}][\cref@result]\thepage}{-}{-}}}% <----- five
273 \@esphack}%
274 \def\label@optarg[#1]#2{%
275 \cref@old@label{#2}%
276 \@bsphack%
277 \protected@edef\@tempa{{page}}{\the\c@page}}% <--- should be protected
278 \setcounter{page}{1}%
279 \protected@edef\@tempb{\thepage}% <--- should be protected
280 \expandafter\setcounter\@tempa%
281 \cref@constructprefix{page}{\cref@result}%
282 \protected@edef\cref@currentlabel{%
283 \expandafter\cref@override@label@type%
284 \cref@currentlabel\@nil{#1}}}%
285 \protected@write\@auxout{%
286 {\string\newlabel{#2\cref}{\cref@currentlabel}%
287 {[\@tempb][\arabic{page}][\cref@result]\thepage}{-}{-}}}% <----- five
288 \@esphack}%
289 }

```

cleveref patches and redefines `\refstepcounter` so that a call updates its data.

This fails if like e.g. in `longtable` the counter is stepped with `\@kernel@refstepcounter`. We therefore move the data setup into the label hook. As the hook is in a group we have to smuggle the data out of it. <https://tex.stackexchange.com/a/722909/2388> and issue #1393

```

290 \newcommand\firstaid@cref@smugglelabel{\let\cref@currentlabel\cref@gcurrentlabel@temp}
291 \newcommand\firstaid@cref@updatelabeldata[1]{%
292 \cref@constructprefix{#1}{\cref@result}%
293 \ifundefined{cref@#1@alias}%
294 {\def\@tempa{#1}}%
295 {\def\@tempa{\csname cref@#1@alias\endcsname}}%
296 \protected@xdef\cref@gcurrentlabel@temp{%
297 [\@tempa][\arabic{#1}][\cref@result]%
298 \csname p@#1\expandafter\endcsname\csname the#1\endcsname}%
299 \aftergroup\firstaid@cref@smugglelabel
300 }

```

we test if `\@currentcounter` is empty for unnumbered sections

```

301 \newif\iftag@
302 \AddToHook{label}[firstaid/cleveref]
303 {\ifx
304 \@currentcounter\@empty
305 \else
306 \iftag@\else
307 \firstaid@cref@updatelabeldata{\@currentcounter}%
308 \fi
309 \fi}

```

Due to a bug correction in `amsmath` a patch in `cleveref` fails in LaTeX 2025-06-01, see gh 1684

```

310 \AddToHook{begindocument}[cleveref]
311 {
312 \IfPackageAtLeastT{amsmath}{2025-05-18}
313 {
314 \def\ltx@label#1{\cref@label{#1}}
315 \def\label@in@display@noarg#1{\cref@old@label@in@display{#1}}
316 \def\label@in@mmeasure@noarg#1{%
317 \begingroup
318 \measuring@false%
319 \cref@old@label@in@display{#1}%
320 \endgroup}%
321 }
322 }

```

Since `\newcounteralias` was introduced, `cleveref`'s sorting mechanism needs to be adapted to check for alias counters.

```

323 \def\cref@isinresetlist#1#2{%
324 \begingroup%
325 %%%% begin change
326 \ifundefined{alias@ctr@#1}
327 {\def\@counter{#1}}
328 {\edef\@counter{\csname alias@ctr@#1\endcsname}}%
329 %%%% end change
330 \def\@elt##1{##1,}%
331 \expandafter\ifx\csname cl@#2\endcsname\relax%
332 \def\cref@resetstack{,\@nil}%

```

```

333 \else%
334 \edef\cref@resetstack{\csname cl@#2\endcsname\noexpand\@nil}%
335 \fi%
336 \let\@nextcounter\relax%
337 \cref@isstackfull{\cref@resetstack}%
338 \@whiles\if@cref@stackfull\fi{%
339 \edef\@nextcounter{\cref@stack@top{\cref@resetstack}}%
340 \ifx\@nextcounter\@counter%
341 \@cref@stackfullfalse%
342 \else%
343 \let\@nextcounter\relax%
344 \cref@stack@pop{\cref@resetstack}%
345 \cref@isstackfull{\cref@resetstack}%
346 \fi}%
347 \ifx\@nextcounter\relax%
348 \def\@next{\@cref@inresetlistfalse}%
349 \else%
350 \def\@next{\@cref@inresetlisttrue}%
351 \fi%
352 \expandafter%
353 \endgroup%
354 \@next}%
355 }
356 \cleveref
357 \kernel

```

2.18 The zref-clever package first aid

As with `cleveref`, the sort code used by `zref-clever` needs to be adapted to check for alias counters. We do this by redefining the property the package uses to store enclosing counters.

```

358 \AddToHook{package/zref-clever/after}[firstaid]%
359 {\input{latex-firstaid-pkg-zref-clever.ltx}}
360 \kernel
361 \*zref-clever
362 \ExplSyntaxOn
363 \FirstAidNeededT{zref-clever}{sty}{2024-11-28~v0.5.1~Clever~LaTeX~cross-references~based~on~z}
364 {
365 \let\Z@E@zc@enclval\relax % so \zref@newprop below doesn't error
366 \zref@newprop {zc@enclval}
367 {
368 \cs_if_exist:cTF {alias@ctr@\l__zrefclever_current_counter_tl}
369 {
370 \__zrefclever_get_enclosing_counters_value:e
371 { \use:c {alias@ctr@\l__zrefclever_current_counter_tl} }
372 }
373 {
374 \__zrefclever_get_enclosing_counters_value:e
375 { \l__zrefclever_current_counter_tl }
376 }
377 }
378 }
379 \ExplSyntaxOff

```

```

380 </zref-clever>
381 <*kernel>

```

2.19 The subcaption package first aid

Inside sub-captions the subcaption package (part of the caption bundle) locally redefines `\label` (in `\caption@subtyphook`) so that every label written there also gets a companion label prefixed with `sub@`, which is what `\subref` reads. Since the correction of a 30-year old typo in `amsmath` (gh/1608) the `\let\label\ltx@label` that `amsmath` appends to `\@arrayparboxrestore` actually takes effect: inside every `\parbox`, `\label` is reset to the meaning saved at `begindocument/end`. As the sub-caption text is typeset inside a `\parbox`, the subcaption version of `\label` is discarded before it can run, the `sub@` labels are silently lost and every `\subref` prints “??” (gh/2172).

The caption bundle is no longer maintained, so as with `cleveref` (gh/1684) we help out here: whenever subcaption redefines `\label` we update the saved `\ltx@label` alongside, so that the reset in `\@arrayparboxrestore` reinstates the subcaption version. Nothing is done unless an `amsmath` with the correction is loaded.

```

382 \AddToHook{package/subcaption/after}[firstaid]{%
383   \FirstAidNeededT{subcaption}{sty}{2023/07/28 v1.6b Sub-captions (AR)}{%
384     \AddToHook{begindocument}[firstaid/subcaption]{%
385       \IfPackageAtLeastT{amsmath}{2025-05-18}{%
386         \g@addto@macro\caption@subtyphook{\let\ltx@label\label}}}}

```

2.20 The arydshln package first aid

Making two internal commands robust to avoid expansion while constructing the array preamble.

```

387 \AddToHook{package/arydshln/after}[firstaid]{%
388   \FirstAidNeededT{arydshln}{sty}{2019/02/21 v1.76 }
389   {%
390     % add \protected
391     \protected\def\adl@vlineL#1#2#3#4{\adl@ivline#4\@nil{#1}{#2}%
392       \xdef\adl@colsL{\adl@colsL
393         \@elt{#3}{\number\@tempcnta}{\number\@tempcntb}%
394         {\adl@dashcolor}{\adl@gapcolor}}}%
395     \protected\def\adl@vlineR#1#2#3#4{\adl@ivline#4\@nil{#1}{#2}%
396       \xdef\adl@colsR{%
397         \@elt{#3}{\number\@tempcnta}{\number\@tempcntb}%
398         {\adl@dashcolor}{\adl@gapcolor}%
399         \adl@colsR}}%
400     \let\adl@act@vlineL\adl@vlineL
401     \let\adl@act@vlineR\adl@vlineR
402     \def\endtabular{\endarray \egroup}
403   }%
404 }

```

2.21 The calc package first aid

The `calc` is not an external package, but for now we are removing a newly introduced incompatibility with `zref-perpage` here. At some point `amstext`, `zref-perpage`,

calc, ... all need to be synced so that they do not overwrite the `\stepcounter` definition but safely hook into the kernel code. But that requires suitable hooks there, so has to wait.

`zref-perpage` already handles `amstext`'s `\iffirstchoice@` in `\stepcounter` so the fix in `calc` should not be applied at `begindocument`. We therefore void it.

```
405 \AddToHook{begindocument}[calc-noop]{}
406 \AddToHook{package/zref-perpage/after}{%
407   \DeclareHookRule{begindocument}{calc-noop}{voids}{calc}}
```

2.22 First aid after retiring the legacy mark mechanism

With the June 2025 release of L^AT_EX the legacy mark mechanism using `\@themark` with exactly two mark components has been removed and replaced by a more general mechanism. This affects a few packages and classes that had patched into the legacy code to extend it or to completely replace it. For now we do our best to keep that working, but mid-term all packages have to update to the new mechanism (and avoid low-level patching) in order to remain compatible with future adjustments.

For an analysis of the current situation see the github issues 1724 at <https://github.com/latex3/latex2e/issues/1724>.

We provide a dummy definition for `\@themark` because some classes expect it to be around. This prevents low-level errors but only helps if the class in question otherwise fully implement its own mark interface (as for example the AMS classes do).

```
408 \def\@themark{}{}
409 \AddToHook{class/smfart/after}[firstaid]{%
410   \FirstAidNeededT{smfart}{cls}{2021/03/28 v1.6
411   Classe LaTeX pour les articles publies par la SMF}
412   {%
413     \def\leftmark{\expandafter\@leftmark\botmark\@empty\@empty}%
414     \def\rightmark{\expandafter\@rightmark\firstmark\@empty\@empty}%
415   }}
416 \AddToHook{class/smfbook/after}[firstaid]{%
417   \FirstAidNeededT{smfbook}{cls}{2021/03/28 v1.6
418   Classe LaTeX pour les monographies editees par la SMF}
419   {%
420     \def\leftmark{\expandafter\@leftmark\botmark\@empty\@empty}%
421     \def\rightmark{\expandafter\@rightmark\firstmark\@empty\@empty}%
422   }}
```

2.23 First aid for morewrites

A recent change in L^AT_EX breaks the `morewrites` package. Below is a possible fix for this. This may not be the final version which is why it is currently placed here (largely to avoid to distribute another full dev release for no good reason).

```
423 \ExplSyntaxOn
424 \cs_set:Npn \__shipout_force_immediate_writes: {
425   \cs_gset_eq:NN \iow_shipout:Nn \iow_now:Nn
426   \cs_gset_eq:NN \lua_shipout:n \lua_now:n
427   \cs_gset_eq:NN \__kernel_write_saved: \write
```

```

428 \cs_gset:Npn \write {\immediate \__kernel_write_saved:}
429 \global\advance\c@page\m@ne
430 }
431 \ExplSyntaxOff

```

2.24 First aid for AMS classes

Some time ago L^AT_EX fully switched to the new mark mechanism. However, the AMS classes still overwrite some, but not all, of the mark commands, i.e., `\leftmark`, `\rightmark`, and `\markboth`, assuming the old mechanism, and this way leaving it in an inconsistent state. We therefore switch the definitions back. The classes should simply stop making these redefinitions (which for a long time serve no purpose).

To support alias counter we must adapt `\@ynthm` in `amsthm` and for the three classes `amsart`, `amsbook` and `amsproc`. This has to be done early enough so that `\newtheorem` calls in the preamble work correctly. As `cleveref` undoes the definition we have to restore them after the package again.

```

432 \ExplSyntaxOn
433 \AddToHook{class/amsart/after}{
434   \DeclareRobustCommand*\markboth[2]{%
435     \mark_insert:nn{2e-left}{#1}
436     \mark_insert:nn{2e-right}{#2}
437     \tl_if_empty:nF{#2}{ \mark_insert:nn{2e-right-nonempty}{#2} }
438   }
439   \cs_set:Npn \leftmark {\mark_use_last:nn{page}{2e-left}}
440   \cs_set:Npn \rightmark {\mark_use_first:nn{page}{2e-right}}
441 }
442 \AddToHook{class/amsproc/after}{
443   \DeclareRobustCommand*\markboth[2]{%
444     \mark_insert:nn{2e-left}{#1}
445     \mark_insert:nn{2e-right}{#2}
446     \tl_if_empty:nF{#2}{ \mark_insert:nn{2e-right-nonempty}{#2} }
447   }
448   \cs_set:Npn \leftmark {\mark_use_last:nn{page}{2e-left}}
449   \cs_set:Npn \rightmark {\mark_use_first:nn{page}{2e-right}}
450 }
451 \AddToHook{class/amsbook/after}{
452   \DeclareRobustCommand*\markboth[2]{%
453     \mark_insert:nn{2e-left}{#1}
454     \mark_insert:nn{2e-right}{#2}
455     \tl_if_empty:nF{#2}{ \mark_insert:nn{2e-right-nonempty}{#2} }
456   }
457   \cs_set:Npn \leftmark {\mark_use_last:nn{page}{2e-left}}
458   \cs_set:Npn \rightmark {\mark_use_first:nn{page}{2e-right}}

```

The `amsbook` class requires more adjustments (`\@secmark` would need to use the new mechanism), but as far as I can see the setup with `\@secmark` is very general but then not really used at all. For example, there is a `\partmark` defined with it but then it is never used. So it all seem to boil down to some fairly simple redefinitions for `\chaptermark` and `\sectionmark` unless I overlooked something. Maybe the reason for this complexity is that the AMS has also some internal classes that make use of the `\@secmark` functionality.

So this is what seems to be needed. Note that the `\chaptermark` puts content in both the left and the right mark, which is a bit unusual but not a bad idea perhaps. However, what is more odd in my opinion is that one can't see if the running header is a chapter title or a section title as both use just single numbers and the same design. But this is what the class does.

```

459 \def\chaptermark#1{\markboth
460   {\thechapter \@ifnotempty{#1}{.~ \MakeUppercase{#1}}}
461   {\thechapter \@ifnotempty{#1}{.~ \MakeUppercase{#1}}}
462 }
463 \def\sectionmark#1{\markright
464   {\thesection \@ifnotempty{#1}{.~ \MakeUppercase{#1}}}
465 }
466 }

467 \newcommand\@amsthm@reset@ynthm
468 {
469   \def\@ynthm##1[##2]##3{%
470     \ifx\relax##2\relax
471       \def\@tempa{\@oparg{\@xthm{##1}{##3}}{}}%
472     \else
473       \ifundefined{c@##2}{%
474         \def\@tempa{\@nocounterr{##2}}%
475       }{%
476         \newcounteralias{##1}{##2}% UF
477         \toks@{##3}%
478         \exp\xdef\csname##1\endcsname{%
479           \@nx\@thm{%
480             \let\@nx\thm@swap
481             \if S\thm@swap\@nx\@firstoftwo\else\@nx\@gobble\fi
482             \exp\@nx\csname th@\the\thm@style\endcsname}%
483             {##1}{\the\toks@}}% UF changed
484           \let\@tempa\relax
485         }%
486       \fi
487       \@tempa}
488   \let\@amsthm@saved@ynthm\@ynthm
489 }

490 \AddToHook{package/amsthm/after}[firstaid/aliascounter]
491 {
492   \@amsthm@reset@ynthm
493   \AddToHook{package/cleveref/after}[firstaid/aliascounter]{\let\@ynthm\@amsthm@saved@ynthm}
494 }

495 \AddToHook{class/amsart/after}[firstaid/aliascounter]
496 {
497   \@amsthm@reset@ynthm
498   \AddToHook{package/cleveref/after}[firstaid/aliascounter]{\let\@ynthm\@amsthm@saved@ynthm}
499 }

500 \AddToHook{class/amsbook/after}[firstaid/aliascounter]
501 {
502   \@amsthm@reset@ynthm
503   \AddToHook{package/cleveref/after}{\let\@ynthm\@amsthm@saved@ynthm}
504 }

505 \AddToHook{class/amsproc/after}[firstaid/aliascounter]
506 {

```

```

507 \amsthm@reset@ynthm
508 \AddToHook{package/cleveref/after}[firstaid/aliascounter]{\let\ynthm\amsthm@saved@ynthm}
509 }
510 \ExplSyntaxOff

```

2.25 The cellspace package first aid

Since this package doesn't seem to see updates we add a firstaid for now, so that it becomes usable again.

```

511 \AddToHook{package/cellspace/after}[firstaid]{%
512 \FirstAidNeededT{cellspace}{sty}{2022/01/04 v1.9.0 Spacing table cells (JN)}%
513 \let\startpbox@action\startpbox}%
514 }
515 </kernel>

```

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
\active@dq	\ifnotempty	\@themark 408
. 191, 192, 199, 200	 460, 461, 464	\@thm 479
\amsthm@reset@ynthm	\ifpackageloaded 50, 57	\@typeset@protect . 213
. 467,	\ifundefined	\@unexpandable@protect
492, 497, 502, 507	 293, 326, 473	 216
\amsthm@saved@ynthm	\@leftmark . . . 413, 420	\@vwid@append 183
. 488,	\@one 145, 167	\@vwid@eqmodefalse . 172
493, 498, 503, 508	\@next 348, 350, 354	\@vwid@eqmodetrue . 173
\auxout 270, 285	\@nextcounter . 336,	\@vwid@offsets 176
\bsphack 264, 276	339, 340, 343, 347	\@vwid@posteqp 173
\@combinefloats . . . 151	\@nil 284,	\@vwid@postw 179
\@counter . 327, 328, 340	332, 334, 391, 395	\@vwid@preeqp 172
\@cref@inresetlistfalse	\@nocounterr 474	\@vwid@resetb 181
. 348	\@onx . . 479, 480, 481, 482	\@vwid@setoffsets . 177
\@cref@inresetlisttrue	\@oparg 471	\@vwid@sift
. 350	\@outputbox@attachfloats	. 161, 169, 175, 185
\@cref@stackfullfalse	 151	\@vwid@toppen 174
. 341	\@par 112	\@whilesw 338
\@currentcounter . .	\@rightmark . . . 414, 421	\@xp 478, 482
. 304, 307	\@secondoffive 260	\@xthm 471
\@elt . 143, 330, 393, 397	\@spaces 12, 13, 14, 15, 16	\@ynthm . . . 469, 488,
\@empty 304,	\@startpbox 513	493, 498, 503, 508
413, 414, 420, 421	\@startpbox@action . 513	_ 208, 370,
\@esphack 273, 288	\@tempa 265,	374, 424, 427, 428
\@firstoffive 254	268, 277, 280,	\ 89
\@firstoftwo 481	294, 295, 297,	
\@gobble 481	471, 474, 484, 487	A
\@hspace 154	\@tempb 267, 272, 279, 287	\acsetup 233
\@ifclassloaded . 64, 71	\@tempcnta . . . 393, 397	\active 208
	\@tempcntb . . . 393, 397	\ActiveUnderscore . 221

\AddToHook		
. 27, 29, 31, 33,		
35, 37, 39, 41,		
43, 45, 47, 52,		
53, 59, 60, 66,		
67, 73, 74, 77,		
79, 81, 84, 86,		
88, 89, 91, 98,		
105, 106, 115,		
139, 148, 153,		
157, 188, 196,		
225, 229, 236,		
239, 244, 261,		
302, 310, 358,		
382, 384, 387,		
405, 406, 409,		
416, 433, 442,		
451, 490, 493,		
495, 498, 500,		
503, 505, 508, 511		
\adl@@vlineL . . . 391, 400		
\adl@@vlineR . . . 395, 401		
\adl@act@@vlineL . . . 400		
\adl@act@@vlineR . . . 401		
\adl@colsL 392		
\adl@colsR 396, 399		
\adl@dashcolor . . . 394, 398		
\adl@gapcolor . . . 394, 398		
\adl@ivline 391, 395		
\advance 167, 429		
\aftergroup 299		
\AfterIncludeFile . . . 80		
\AfterIncludes 34		
\arabic 272, 287, 297		
\AtBeginOfClasses . . . 40		
\AtBeginOfClassFile . . . 62		
\AtBeginOfEveryFile . . . 26		
\AtBeginOfFile 44		
\AtBeginOfIncludeFile		
. 76		
\AtBeginOfIncludes . . . 30		
\AtBeginOfPackageFile		
. 48		
\AtBeginOfPackages . . . 36		
\AtEndOfClasses 42		
\AtEndOfClassFile . . . 69		
\AtEndOfEveryFile . . . 28		
\AtEndOfFile 46		
\AtEndOfIncludeFile . . . 78		
\AtEndOfIncludes 32		
\AtEndOfPackageFile . . . 55		
\AtEndOfPackages 38		
	B	D
	\BabelCaseHack 105	\declare@file@substitution
	\begingroup . . . 86, 124,	 23
	154, 207, 317, 324	\DeclareDocumentCommand
	\botmark 413, 420	 48, 55, 62, 69
	\BreakableUnderscore	\DeclareHookRule . . . 407
	 214	\DeclareRobustCommand
		 434, 443, 452
	C	\def . . . 2, 3, 105, 143,
	\c@page 265, 277, 429	154, 161, 192,
	\caption@subtyhook	200, 249, 251,
	 386	255, 257, 262,
	\catcode 208	274, 294, 295,
	\chaptermark 459	314, 315, 316,
	\count 140, 141, 144	323, 327, 330,
	\count@ 165, 172,	332, 348, 350,
	173, 174, 176, 179	391, 395, 402,
	\cpageref@getref . . . 255	408, 413, 414,
	\cref@constructprefix	420, 421, 459,
	 269, 281, 292	463, 469, 471, 474
	\cref@currentlabel .	\dimen 122, 123
	 271,	\dimen@ 164
	282, 284, 286, 290	
	\cref@currentlabel@temp	E
	 290, 296	\edef . . . 155, 328, 334, 339
	\cref@getref 249	\egroup 402
	\cref@isinresetlist . . . 323	\else 118,
	\cref@isstackfull 337, 345	119, 167, 176,
	\cref@label 314	178, 180, 212,
	\cref@old@label . . . 263, 275	214, 215, 217,
	\cref@old@label@in@display	305, 306, 333,
	 315, 319	342, 349, 472, 481
	\cref@override@label@type	\endarray 402
	 283	\endcsname . . . 250, 256,
	\cref@resetstack 332, 334,	295, 298, 328,
	337, 339, 344, 345	331, 334, 478, 482
	\cref@result . . . 269, 272,	\endgroup 135,
	281, 287, 292, 297	155, 222, 320, 353
	\cref@stack@pop 344	\endtabular 402
	\cref@stack@top 339	\exp 9, 18
	\CROP@genreflect . . . 120	\expandafter . . . 145, 250,
	\CROP@horigin 122	251, 252, 253,
	\cs 8, 92,	254, 256, 257,
	93, 94, 99, 100,	258, 259, 260,
	101, 368, 424,	268, 280, 283,
	425, 426, 427,	298, 331, 352,
	428, 439, 440,	413, 414, 420, 421
	448, 449, 457, 458	\ExplSyntaxOff . . . 20, 96,
	\csname 250, 256,	104, 379, 431, 510
	295, 298, 328,	\ExplSyntaxOn 7,
	331, 334, 478, 482	90, 97, 362, 423, 432
		F
		\fi 118, 119, 142,
		146, 163, 167,

171, 172, 173, 182, 184, 214, 218, 219, 308, 309, 335, 338, 346, 351, 481, 486	K <code>\kern</code> 123	<code>\newcounteralias</code> .. 476 <code>\newif</code> 301 <code>\newlabel</code> 271, 286 <code>\ngermanTeX</code> 201 <code>\noexpand</code> 216, 334 <code>\number</code> ... 145, 393, 397 <code>\numexpr</code> 145
<code>\firstaid@cref@smugglelabel</code> 386 290, 299 <code>\firstaid@cref@updatelabeldata</code> 315 291, 307 <code>\FirstAidNeededT</code> 7, 85, 107, 116, 149, 158, 189, 197, 226, 230, 240, 248, 363, 383, 388, 410, 417, 512 <code>\firstmark</code> ... 414, 421 <code>\FN@allmarks</code> .. 143, 145	L <code>\l</code> 368, 371, 375 <code>\label</code> 316 <code>\label@in@display@noarg</code> 262 <code>\label@in@mmeasure@noarg</code> 274 <code>\label@noarg</code> 166 <code>\label@optarg</code> 164 <code>\lastbox</code> 165 <code>\lastkern</code> 162, 163 <code>\lastpenalty</code> 2, 5 <code>\lastskip</code> 314, 386 <code>\LaTeXFirstAidDate</code> 2, 5 <code>\LaTeXFirstAidVersion</code> 3, 5 <code>\leavevmode</code> 121 <code>\leftmark</code> 413, 420, 439, 448, 457 <code>\let</code> .. 110, 112, 151, 169, 175, 191, 199, 221, 250, 256, 290, 336, 343, 365, 386, 400, 401, 480, 484, 488, 493, 498, 503, 508, 513 <code>\ltx@label</code> ... 314, 386 <code>\lua</code> 426	O <code>\obeyedline</code> 110 <code>\obeylines</code> 111
G <code>\g@addto@macro</code> 386 <code>\gdef</code> 209 <code>\germanTeX</code> 193 <code>\global</code> ... 141, 221, 429 <code>\grmn@active@dq@</code> 191, 192, 199, 200	M <code>\m@ne</code> 429 <code>\MakeUppercase</code> 460, 461, 464 <code>\mark</code> 435, 436, 437, 439, 440, 444, 445, 446, 448, 449, 453, 454, 455, 457, 458 <code>\markboth</code> 434, 443, 452, 459 <code>\markright</code> 463 <code>\mathcode</code> 89 <code>\measuring@false</code> .. 318	P <code>\PackageWarning</code> ... 170 <code>\paperheight</code> .. 119, 128 <code>\paperwidth</code> ... 118, 127 <code>\pgfhookintoshipout</code> 99 <code>\pgfpages@interceptshipout</code> 94, 101 <code>\pgfpages@originalshipout</code> 92, 93, 100 <code>\protect</code> 192, 200, 213, 216, 217 <code>\protected</code> 209, 390, 391, 395 <code>\protected@edef</code> 265, 267, 277, 279, 282 <code>\protected@write</code> 270, 285 <code>\protected@xdef</code> ... 296 <code>\ProvidesFile</code> 4 <code>\ProvidesPackage</code> .. 206
H <code>\hb@xt@</code> 127 <code>\hskip</code> 155 <code>\hss</code> 132	I <code>\if</code> 481 <code>\if@cref@stackfull</code> . 338 <code>\IfBooleanTF</code> 49, 56, 63, 70 <code>\ifdim</code> 118, 119, 163 <code>\ifincsname</code> 210 <code>\ifmmode</code> 214 <code>\ifnum</code> 140, 144, 168, 172, 173, 174, 176, 179 <code>\IfPackageAtLeastT</code> 312, 385 <code>\iftag@</code> 301, 306 <code>\ifvoid</code> 167 <code>\ifx</code> .. 213, 216, 303, 331, 340, 347, 470 <code>\immediate</code> 428 <code>\input</code> 245, 359 <code>\insec@unt</code> 140, 141 <code>\iow</code> 425	R <code>\reflectbox</code> 126 <code>\relax</code> 155, 169, 175, 331, 336, 343, 347, 365, 470, 484 <code>\renewcommand</code> . 109, 120 <code>\RequirePackage</code> 226, 237 <code>\rightmark</code> ... 414, 421, 440, 449, 458
S <code>\sb</code> 214 <code>\SB@@par</code> 112 <code>\SB@obeylines</code> 109 <code>\SB@par</code> 110 <code>\sectionmark</code> 463 <code>\set@typeset@protect</code> 125 <code>\setbox</code> 166 <code>\setcounter</code> 266, 268, 278, 280 <code>\setlength</code> 154	N <code>\newcommand</code> 26, 28, 30, 32, 34, 36, 38, 40, 42, 44, 46, 76, 78, 80, 290, 291, 467	

\shipout	92	\thepage		V	
\sift@deathcycles		. 267, 272, 279, 287		\vbox	128
.	167, 168	\thesection	464	\vss	130
\skip@	154, 155, 162	\thm@style	482		
\space	5, 159	\thm@swap	480, 481	W	
\stockheight	119	\tl	437, 446, 455	\write	427, 428
\stockwidth	118	\toks@	477, 483		
\str	9, 18	\typeout	10, 11	X	
\string	211, 271, 286			\x	155
		U		\xdef	392, 396, 478
		\unkern	164		
T		\unpenalty	165	Z	
\tex	93, 94, 100, 101	\unskip	162, 163	\z@	163, 166, 167, 181
\the	155,	\use	15, 371	\Z@E@zc@enclval	365
.	265, 277, 482, 483	\UseName	232, 242	\zref@newprop	365, 366
\thechapter	460, 461				