The `latex-lab-mathtools` code*

LaTeX Project

v0.80e 2026-04-25

Abstract

Contents

1 Introduction **1**

2 The Implementation **1**

2.1 File declaration 1

2.2 `\shortintertext` 1

Index **5**

1 Introduction

This file implements adaptions to the mathtools package needed for the tagging project.

2 The Implementation

```
1 ⟨@@=math⟩

2 ⟨*kernel⟩
```

2.1 File declaration

```
3 \ProvidesFile{latex-lab-mathtools.ltx}
4         [\ltlabmathtoolsdate\space \ltlabmathtoolsversion\space mathtools adaptions]
```

*

2.2 \shortintertext

Similar to the \intertext command from amsmath, \shortintertext errors with active tagging as it is processed twice which leads to duplicated structures. The fix is similar but is complicated as mathtools defines two version (and an additional \intertext version) and package options to switch between the variants.

At first we redefine all the internal commands

```
\ExplSyntaxOn
\tl_new:N\l__math_mathtools_init_tl
\cs_if_eq:NNTF\intertext@ \MT_intertext:
  {
    \tl_set:Nn \l__math_mathtools_init_tl {\MT_orig_intertext_false:}
  }
  {
    \tl_set:Nn \l__math_mathtools_init_tl {\MT_orig_intertext_true:}
  }
\cs_if_eq:NNTF\shortintertext@ \MT_shortintertext:n
  {
    \tl_put_right:Nn \l__math_mathtools_init_tl
      {\MT_orig_shortintertext_false:}
  }
  {
    \tl_put_right:Nn \l__math_mathtools_init_tl
      {\MT_orig_shortintertext_true:}
  }
⟨@@=⟩
\def\MT_intertext: {%
  \def\intertext##1{%
    \ifvmode\else\\\@empty\fi
    \noalign{%
      \penalty\postdisplaypenalty\vskip\belowdisplayskip
      \vskip-\lineskiplimit      % CCS
      \vskip\normallineskiplimit % CCS
      \vskip\l_MT_above_intertext_sep
       \vbox{%
```

Stop tagging when measuring:

```
      \ifmeasuring@\tag_suspend:n{\measuring}\fi
      \normalbaselines
        \ifdim
          \ifdim\@totalleftmargin=\z@
            \linewidth
          \else
            -\maxdimen
          \fi
         =\columnwidth
       \else \parshape\@ne \@totalleftmargin \linewidth
       \fi
```

End the previous mc:

```
       \UseTaggingSocket{math/intertext}{}
```

```
        {\noindent\ignorespaces##1\par}
       }%
      \penalty\predisplaypenalty\vskip\abovedisplayskip%
      \vskip-\lineskiplimit      % CCS
      \vskip\normallineskiplimit % CCS
      \vskip\l_MT_below_intertext_sep
   }%
 }%
 \MH_let:NwN \shortintertext \shortintertext@
}

\def\MT_orig_shortintertext:n #1{%
  \ifvmode\else\\\@empty\fi
  \noalign{%
    \penalty\postdisplaypenalty\vskip\abovedisplayshortskip
    \vbox{%
      \ifmeasuring@\tag_suspend:n{\measuring}\fi
      \normalbaselines
      \MH_if_dim:w
        \MH_if_dim:w \@totalleftmargin=\z@
          \linewidth
        \MH_else:
          -\maxdimen
        \MH_fi:
        =\columnwidth
      \MH_else:
        \parshape\@ne \@totalleftmargin \linewidth
      \MH_fi:

      \UseTaggingSocket{math/intertext}{}
       {\noindent\ignorespaces#1\par}
    }
    \penalty\predisplaypenalty\vskip\abovedisplayshortskip%
  }%
}

\def\MT_shortintertext:n #1{%
  \ifvmode\else\\\@empty\fi
  \noalign{%
    \penalty\postdisplaypenalty\vskip\abovedisplayshortskip
    \vskip-\lineskiplimit
    \vskip\normallineskiplimit
    \vskip\l_MT_above_shortintertext_sep
    \vbox{%
    \ifmeasuring@\tag_suspend:n{\measuring}\fi
    \normalbaselines
      \MH_if_dim:w
        \MH_if_dim:w \@totalleftmargin=\z@
          \linewidth
        \MH_else:
          -\maxdimen
        \MH_fi:
        =\columnwidth
      \MH_else:
        \parshape\@ne \@totalleftmargin \linewidth
```

```
      \MH_fi:

      \UseTaggingSocket{math/intertext}{}
       {\noindent\ignorespaces#1\par}
    }%
    \penalty\predisplaypenalty\vskip\abovedisplayshortskip%
    \vskip-\lineskiplimit
    \vskip\normallineskiplimit
    \vskip\l_MT_below_shortintertext_sep
  }%
}
```

see https://github.com/latex3/tagging-project/issues/734. The multlined environment still creates a few unneeded structure, perhaps triggered by empty tags.

```
    \renewcommand*\MT_mult_internal:n [1]{
     \MH_if_boolean:nF {outer_mult}{\alignedspace@left} %<-- requires amsmath 2016/11/05
      \MT_next:
      \bgroup
        \Let@
        \def\l_MT_multline_lastline_fint{0 }
        \chardef\dspbrk@context\@ne \restore@math@cr
        \MH_let:NwN \math@cr@@\MT_mult_mathcr_atat:w
        \MH_let:NwN \shoveleft\MT_shoveleft:wn
        \MH_let:NwN \shoveright\MT_shoveright:wn
        \spread@equation
        \MH_set_boolean_F:n {mult_firstline}
        \MT_measure_mult:n {#1}
        \MH_if_dim:w \l_MT_multwidth_dim<\l_MT_multline_measure_fdim
          \MH_setlength:dn \l_MT_multwidth_dim{\l_MT_multline_measure_fdim}
        \fi
        \MH_set_boolean_T:n {mult_firstline}
        \MH_if_num:w \l_MT_multline_lastline_fint=\@ne
          \MH_let:NwN \math@cr@@\MT_mult_firstandlast_mathcr:w
        \MH_fi:
        \ialign\bgroup
          \hfil\strut@$\m@th\displaystyle{}##
          \UseTaggingSocket{math/luamml/save/nNn}{ {} \displaystyle {mtd}}
          $
          \UseTaggingSocket{math/luamml/mtable/finalizecol}{last}
          \hfil
          \crcr
          \hfilneg
          #1
    }
```

end hook

```
⟨@@=math⟩

  \l__math_mathtools_init_tl
\ExplSyntaxOff

⟨/kernel⟩
```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols

\\ 26, 56, 79

A

\abovedisplayshortskip . . . 58, 75, 81, 101
\abovedisplayskip 47

B

\belowdisplayskip 28
\bgroup 110, 127

C

\chardef 113
\columnwidth 41, 68, 94
\crcr 133
cs commands:
\cs_if_eq:NNTF 7, 14

D

\def 24, 25, 55, 78, 112
\displaystyle 128, 129

E

\else 26, 38, 42, 56, 79
\ExplSyntaxOff 139
\ExplSyntaxOn 5

F

\fi 26, 33, 40, 43, 56, 60, 79, 86, 122

H

\hfil 128, 132
\hfilneg 134

I

\ialign 127
\ifdim 35, 36
\ifvmode 26, 56, 79
\ignorespaces 45, 73, 99
\intertext *1*, 25

L

\lineskiplimit 29, 48, 82, 102
\linewidth 37, 42, 64, 70, 90, 96
\ltlabmathtoolsdate 4
\ltlabmathtoolsversion 4

M

\maxdimen 39, 66, 92
\measuring 33, 60, 86
MH commands:
\MH_else: 65, 69, 91, 95
\MH_fi: 67, 71, 93, 97, 126
\MH_if_boolean:nTF 108
\MH_if_dim:w 62, 63, 88, 89, 120
\MH_if_num:w 124
\MH_let:NwN 53, 114, 115, 116, 125
\MH_set_boolean_F:n 118
\MH_set_boolean_T:n 123
\MH_setlength:dn 121
MT commands:
\l_MT_above_intertext_sep 31
\l_MT_above_shortintertext_sep . . 84
\l_MT_below_intertext_sep 50
\l_MT_below_shortintertext_sep . 104
\MT_intertext: 7, 24
\MT_measure_mult:n 119
\MT_mult_firstandlast_mathcr:w . 125
\MT_mult_internal:n 107
\MT_mult_mathcr_atat:w 114
\l_MT_multline_lastline_fint 112, 124
\l_MT_multline_measure_fdim 120, 121
\l_MT_multwidth_dim 120, 121
\MT_next: 109
\MT_orig_intertext_false: 9
\MT_orig_intertext_true: 12
\MT_orig_shortintertext:n 55
\MT_orig_shortintertext_false: . . 17
\MT_orig_shortintertext_true: . . . 21
\MT_shortintertext:n 14, 78
\MT_shoveleft:wn 115
\MT_shoveright:wn 116

N

\noalign 27, 57, 80
\noindent 45, 73, 99
\normalbaselines 34, 61, 87
\normallineskiplimit 30, 49, 83, 103

P

\par 45, 73, 99
\parshape 42, 70, 96
\penalty 28, 47, 58, 75, 81, 101
\postdisplaypenalty 28, 58, 81
\predisplaypenalty 47, 75, 101
\ProvidesFile 3

R

\renewcommand 107

S

\shortintertext *1*, 53
\shoveleft 115
\shoveright 116
\space 4

T

tag commands:
\tag_suspend:n 33, 60, 86
TEX and LATEX 2ε commands:
\@empty 26, 56, 79
\@ne 42, 70, 96, 113, 124
\@totalleftmargin 36, 42, 63, 70, 89, 96
\alignedspace@left 108
\dspbrk@context 113
\ifmeasuring@ 33, 60, 86
\intertext@ 7
\Let@ 111
\m@th 128
\math@cr@@ 114, 125
\restore@math@cr 113
\shortintertext@ 14, 53
\spread@equation 117
\strut@ 128
\z@ 36, 63, 89
tl commands:
\tl_new:N 6
\tl_put_right:Nn 16, 20
\tl_set:Nn 9, 12
tl internal commands:
\l__math_mathtools_init_tl . . . .
. . . . . 6, 9, 12, 16, 20, 138

U

\UseTaggingSocket . . . 44, 72, 98, 129, 131

V

\vbox 32, 59, 85
\vskip . . . 28, 29, 30, 31, 47, 48, 49, 50,
58, 75, 81, 82, 83, 84, 101, 102, 103, 104